



NEW

UM-FXAH-CB with FXAH-120



UM-FXAH-CB

max. 150 kg/330 lbs

UNIMOBIL UM-FXAH-CB Laying Dolly

Fast and ergonomic lifting, moving and laying of large or up to two absorbent concrete slabs, natural stone, tiles and other absorbent building materials.

With two optionally available FXAH-120-GRABO-GREENLINE or two FXAH-120-GRABO-PRO-LIFTER-GREENLINE vacuum lifters, the UM-FXAH-CB becomes a one-man device for suction-tight building materials.

The vacuum lifters attach themselves when placed on the slab or tile. The release process is triggered simultaneously on both vacuum lifters by operating a hand lever.

- One-person operation possible by controlling the extension arm or the removal process via hand lever.
- Possibility to pick up larger single slabs, tiles or 2 smaller slabs/tiles up to a total weight of 150 kg.
- Quick and easy attachment of the FXAH vacuum lifters without tools using spring latches.
- The distance between the FXAH vacuum lifters is adjustable from 200 mm to 800 mm.
- Telescopic arm and handle.
- Durable surface protection by galvanizing.



Type	Description	Dimensions L x W mm (in)	Battery Capacity Ah	Type of Drive electric/Battery kW	Working Width mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
UM-FXAH-CB	UNIMOBIL base unit with CB crossbar and 2 adapters for FXAH-120, including Bowden cable. <i>Available from Q2/2024</i>				200 – 800 (7.87 – 31.49)	64 (141)	150 (331)	42740018
FXAH-120-GRABO-GREENLINE		300 x 180 (11.81 x 7.09)	2.2	0.0016		2.5 (5.51)	120 (265)	58500016
FXAH-120-GRABO-PRO-LIFTER-GREENLINE		300 x 180 (11.81 x 7.09)	2.2	0.0016		5.5 (12)	120 (265)	58500014

Accessories:

Type	Working Width mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
UM-FXAH-CB Retrofit kit	200 – 800 (7.87 – 31.49)	19 (42)	150 (331)	42740019

5

011223 Technical data contained in this catalogue can be modified without prior notice in the interest of progress. Illustrations are exemplary and non-binding. No liability accepted for any misprints, mistakes and errors. * Details in the general sales conditions at the end of the catalogue or at www.probst-handling.com/en/gtc.