



SVZ-UNI-VARIO



SVZ-UNI-VARIO

Manhole and Cone Installation Clamp SVZ-UNI-VARIO

With the SVZ-UNI-VARIO manhole and cone installation clamp, even cones hang on exact level. The detachment takes place via an automatic trip mechanism.

Some sealing systems absolutely require the installation of cones in an precisely vertical position. This is possible for cones of every shape and size thanks to Integral centre of gravity adjustment. Diameter adjustable in degrees as follows: 625/700/800/1,000/1,050/1,200/1,250/1,350/1,500 mm (24.60/27.55/31.49/39.37/41.33/47.24/49.21/53.14/59 inch).

- Manhole rings and centric cones are laid horizontally without shifting the suspension point. By switching via the guides on the suspension, the excavator driver can control the automatic shift of the suspension point for laying asymmetric cones.
- Fully automatic trip mechanism for switch-over from „full“ to „empty“.
- A rearrangement of the settings is not necessary when handling manhole rings and cones, as the SVZ-UNI-VARIO has got two gripping levels.
- Universally suitable for manhole basers, rings (height 500 mm/19.68 inch or larger) and cones.
- Ultimate safety in gripping by means of self-tensioning steel claws.
- Durable surface protection by galvanizing.

Type	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
SVZ-UNI-VARIO	625 – 1,500 (24.61 – 59.06)	148 (326)	2,500 (5,512)	54000041

011223 Technical data contained in this catalogue can be modified without prior notice in the interest of progress. Illustrations are exemplary and non-binding. No liability accepted for any misprints, mistakes and errors. * Details in the general sales conditions at the end of the catalogue or at www.probst-handling.com/en/gtc