



## Angled Suction Plates WSP

For direct coupling to the operating valve unit, hose cylinder extension or quick-change device.

Suction plates with attached foam rubber seal, including lifter for tactile steering. Other suction plates on request.

WSP

Type	Dimensions L x W x H mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL -420 mbar kg (lbs)	Angle ° Degree	Order-Number
WSP-150-52/15-12-98°	520 x 150 x 120 (20.47 x 5.91 x 4.72)	4.7 (10)	150 (331)	98	52500184
WSP-150-70/8-11-143°	700 x 80 x 110 (27.56 x 3.15 x 4.33)	6 (13)	150 (331)	143	42100238
WSP-150-70/11-17-143°	700 x 110 x 170 (27.56 x 4.33 x 6.69)	6 (13)	150 (331)	143	42100126
WSP-150-85/7-7-135°	850 x 70 x 70 (33.46 x 2.76 x 2.76)	6 (13)	150 (331)	135	52300018
WSP-150-70/13-10-143°	700 x 130 x 100 (27.56 x 5.12 x 3.94)	6 (13)	150 (331)	143	52500131
WSP-150-90/10-14-93°	900 x 100 x 140 (35.43 x 3.94 x 5.51)	7 (15)	150 (331)	93	52300033
WSP-150-90/8-11-90°	900 x 80 x 110 (35.43 x 3.15 x 4.33)	7.5 (17)	150 (331)	90	42100795

Please note: To ensure that the detachment safety device functions properly, suction plates with a lower load capacity than the lifting unit HE allows must not be used. The use of suction plates with a higher load capacity than that of the lifting unit is permitted.



## Multiple Suction Plate MSP-3-S-150-3x22Rd

Easy lifting and laying of concrete blocks.

With the 3-fold suction plate, concrete block paving can be laid effortlessly.

- Suitable for Probst lifting units up to HE-150.
- The distance between the suction plates can be adjusted with screws.
- Quickly replaceable sealing rings with low-wear sponge rubber.



MSP 3-way (rigid)

Type	Dimensions oval, L x B mm (in)	Number of Suction Plates Pcs.	Dead Weight kg (lbs)	Working Load Limit/WLL -420 mbar kg (lbs)	Order-Number
MSP-3-S-150-3x22Rd	220 (8.66)	3	9.9 (22)	150 (331)	42101192