



FMK



FMK

FLEXMARKER-KIT FMK

The **FLEXMARKER-KIT FMK** is a complete system to shape and mark tailor-made curves. Creating dynamically shaped paths without visual interruptions.

Work mode 1: For paths and bed edges, the so called one-liner, are laid in dry concrete. For that purpose the FLEXMARKER-KIT FMK can be fixed at the pins with the clamps. It doesn't only show the curve, it also shows the vertical profile.

Work mode 2: The interconnecting fiberglass rods can be securely fixed on the existing pavement with the fixing claws. The curve can be marked by spray paint or chalk (e.g. PAVERMARKER PM of Probst). Weighted by paving stones, the claws are immovably fixed.

- Harmonious curves can be prepared quickly and with enormous time savings.
- Smallest bending radius 15 cm (6 inch).

Scope of delivery:

FMK: Set consisting of 10 fiberglass rods, 5 fixing claws and 10 clamps.

Type	Dead Weight kg (lbs)	Order-Number
FMK	3.1 (6.83)	51800074



SF

SAFEFLEX SF

The innovative clamping fixture for cutting stone safely.

The risk of cuts can be reduced considerably with the SAFEFLEX SF. It can secure building materials such as cobblestones and natural flagstones quickly and safely. This makes cutting with the angle grinder easier, safer and more precise. To secure the building material, the user pushes on the top clamping element with one foot. When the user takes their foot off the non-slip tread, springs push the clamping elements apart again and the building material can be removed.

- Elevation of the material being cut, so cutting wheel does not go into the ground.
- Non-slip mat to prevent stones from sliding sideways.
- Fast and simple adjustment of stone thickness in using 2 lateral locking bars.
- Individually adjustable height of the SAFEFLEX with 4 screws that can be turned in on the bottom.
- Suitable for right and left-handed use.
- Fast fixation without additional tools.
- Saves material since smaller "offcuts" can be safely secured, even with a small supporting surface.
- Easy to transport since the SAFEFLEX is much smaller than a wet cutting bench for example.
- Durable surface protection by galvanizing.



Type	Dead Weight kg (lbs)	Height Adjustable Range mm (in)	Clamping Range mm (in)	Order-Number
SF	7.1 (16)	10 (0.39)	30 – 160 (1.18 – 6.30)	51210001