



### Multiple Forks MFD

For picking up several concrete pipes at the same time.

The device is lifted using the fork lift truck forks, with a lockpin on the forks. Distance between the bells of the pipes: 20 mm (0.78 inch). On request additional price for plastic lining of forks to protect the pipes.

- The spreader bar is lined with rubber so that the pipes cannot be damaged.
- Ideal for stacking the storage area and for loading trucks.

MFD

Type	Number of Pipes Pcs.	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Hydraulic Connection Pressure bar (psi)	Length Stone/Element mm (in)	Working Load Limit/ WLL kg (lbs)	Order-Number
MFD-25-5	5	250 (9.84)	300 (661)		2,000 – 3,000 (78.74 – 118.11)	2,600 (5,732)	57400001
MFD-30-5	5	300 (11.81)	330 (728)		2,000 – 3,000 (78.74 – 118.11)	2,000 (4,409)	57400085
MFD-40-4	4	400 (15¾)	350 (772)		2,000 – 3,000 (78.74 – 118.11)	2,200 (4,850)	57400086
MFD-50-3	3	500 (19.69)	375 (827)		2,000 – 3,000 (78.74 – 118.11)	2,500 (5,512)	57400104
MFD-60-3	3	600 (23.62)	400 (882)		2,000 – 3,000 (78.74 – 118.11)	4,300 (9,480)	57400026
MFD-UNI	5	300 – 600 (11.81 – 23.62)	1,200 (2,646)	180 – 210 (2,611 – 3,046)	2,000 – 3,000 (78.74 – 118.11)	5,000 (11,023)	57400067



### Manhole Ring Clamp RK-XL-IV/-V/-VI

With the mechanical large pipe clamp, concrete pipes up to ID 2800 mm (110 inch) can be safely grabbed vertically after production and placed on a tilting table.

- Fully mechanical operation, making it suitable for use with any lifting equipment.
- Adjustable to the dimensions of the pipe in a hand crank.
- Crane eye for attaching to crane hook.
- Fully automatic change-over from “full” to “empty”, making it an absolute one-man machine.

RK

Type	Number of Claws Pcs.	Diameter Nominal Diameter mm (in)	Inside Height mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/ WLL kg (lbs)	Order-Number
RK-XL-IV	2	1,000 – 1,800 (39.37 – 70.87)	750 (29.53)	600 (1,323)	110 – 240 (4.33 – 9.45)	7,500 (16,535)	57300001
RK-XL-V	2	1,500 – 2,600 (59.06 – 102.36)	1,000 (39.37)	1,700 (3,748)	110 – 280 (4.33 – 11.02)	15,000 (33,069)	57300002
RK-XL-VI	2	1,500 – 2,800 (59.06 – 110.24)	1,000 (39.37)	2,680 (5,908)	100 – 300 (3.94 – 11.81)	25,000 (55,116)	57300009