




Manhole Ring Clamp RK-I/-II/-III

Also suitable for manhole rings (DIN 4034 Part 1 and 2) due to its extra-deep claws and rubber supports.

Adjusted to the dimensions of the manhole ring by bolts. As only the side wall is gripped, no radial pressure is exerted. Making it suitable for handling green products.

- Fully mechanical operation, so it can be used with any lifting equipment.
- Crane eye for attaching to crane hook.
- Equipped with 2 or 3 grippers, according to model.
- Fully automatic change-over from “full” to “empty”, making it an absolute one-man machine.

RK + ET



top: ET Low level fork sleeves, bottom: ET

Type	Number of Claws Pcs.	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
RK-I	2	800 – 1,500 (31½ – 59)	170 (375)	80 – 160 (3¼ – 6¼)	2,000 (4,400)	57200030
RK-I-US	2	60 – 180 (2¼ – 7)	240 (530)	914 – 1,524 (36 – 60)	3,200 (7,100)	57200032
RK-II	3	1,500 – 2,500 (59 – 98½)	320 (710)	80 – 160 (3¼ – 6¼)	3,000 (6,600)	57200033
RK-III	3	2,000 – 3,000 (78¾ – 118)	350 (770)	80 – 160 (3¼ – 6¼)	3,000 (6,600)	57200036

Accessories

ET-RK with cross link / ET-RK swivel hook: Fork sleeve for fork lift peaks. Suitable for the RK, off set design to save lifting height.

ET with cross link / ET 90° incl. cross link / ET with cross link USA: Fork sleeve for fork lift peaks. Suitable for RK or other devices, mounted directly above the gripper including lifting eye for attaching to crane hook. ET 90° design with manual turning device which arrests itself every 90°.

Type	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
ET-RK with cross link	130 (285)	3,500 (7,700)	47200002
ET-RK swivel hook	140 (310)	3,500 (7,700)	47200028
ET with cross link	65 (145)	4,000 (8,800)	47100010
ET 90° incl. cross link	65 (145)	4,000 (8,800)	47110002
ET with cross link USA	65 (145)	4,000 (8,800)	47100106