



SH-2500-GREENLINE

max. 2,500 kg

Vacuum Lifting Device SH-2500-GREENLINE

The classic now also with battery power. Powerful and independent of mains power.

Suitable for predominantly non-porous concrete and natural stone elements

Fitted as standard with load securing chain

Powered by a 24 V lithium-ion rechargeable battery. (exchangeable battery concept) can operate up to 6 hours.

Can be equipped with a hydraulic rotator as an add-on if requested.

■ Emission-free and low-noise operation.

Scope of delivery

SH-2500-GREENLINE: 1 x rechargeable battery and a 230 V/50 Hz charger.

The charging time is approx. 2.5 hours

SH-2500-GREENLINE-FFS: As SH-2500-GREENLINE, but with additional remote control for suction and release.



5

SH-2500-HGV: Should be used when laying elements wider than 1 meter, in order to keep operators feet in safe distance from load.

Handle Extension SH-2500-HGV can be fitted at any time later to the structure of SH-2500 by bolting it on with brackets.

SH-2500-RS: To extend the working radius of Micro Jumbo MJ at any time, we recommend the solid set of wheels for later equipment. Easy mounting to the lifting unit SH-2500. The wheelset consists of two attachable main wheels, diameter 300 mm, one foldable support-wheel and one swivelling wheel. Later attachment to the basic device SH is no problem.

Type	Description	Battery Capacity Ah	Type of Drive electric/Battery kW	Working Voltage V	Dead Weight kg (lbs)	Working Load Limit/WLL -600 mbar kg (lbs)	Order-Number
SH-2500-GREENLINE	Basic device, without suction plate	23	0.4	24	151 (335)	2,500 (5,500)	52400046
SH-2500-GREENLINE-FFS	Basic device, without suction plate. With remote control	23	0.4	24	151 (335)	2,500 (5,500)	52400048

Accessories

Type	Description	Order-Number
Battery-24V/23Ah	Spare storage battery for SH-2500-GREENLINE	24200142
SH-2500-HGV	Handle extension for all models SH-2500	42400088
SH-2500-RS	Wheelset for all models SH-2500	42500299

For suction plates see page 88.