

1



VTK-V with supporting wheel



VTK-V with AR

## Adjustable Paver Transport Cart VTK-V

For the effortless transportation of bound or loose pavers, kerb stones, slabs, etc.

Clamping is done by operating a lever 90° (maximum pressure 15 kg).

Adjustable gripping width from 550 mm – 1,050 mm.

The minimum and maximum gripping widths can be altered using special grippers.

- An integral protection device prevents overloading of the clamping mechanism.
- A favourable load distribution and the light-weight-nature of the device ensures optimal operating.
- Its narrow build means it can be used on the smallest building sites.
- Blocks can easily be loaded from the pallet without the need of a ramp.
- Fully mechanical.
- Adjusts smoothly and without the need for tools.
- Durable galvanized surfaces.

Type	Length of Gripper mm (in)	Dead Weight kg (lbs)	Height Stone/Element mm (in)	Clamping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
VTK-V	200 (7¾)	68 (150)	900 (35½)	550 – 1,050 (21¾ – 41¼)	400 (880)	51100015

### Accessories

Type	Description	Dead Weight kg (lbs)	Order-Number
VTK-V-AR	Access ramp for VTK-V, to make picking up interlocking paving stones on the pallet easier. L = 700 mm, W = 850 mm, H = 160 mm	10 (20)	51100014
VTK-V-SR/N	Supporting wheel for easy handling on even ground. Can be additionally attached at any time.	7 (15)	41100041