



Rotating Clamp for Concrete Pipes WG-R

A novel method for rotation of several pipes in one operational sequence, regardless of accuracy of individual pipes interspace.

Length of rubber grippers L = 1,650 mm.

Supplied without connecting hose to the fork-lift-truck.

- The clamp attachment enables the rotating of the pipes by +_ 90° (rotating range 360° endless) – without shunting the forklift.
- It is possible to pick up 3 pipes.

WG

| Type | Diameter outside mm (in) | Dead Weight kg (lbs) | Hydraulic Connection Pressure bar (psi) | Working Load Limit/WLL kg (lbs) | Order-Number |
|--------------|----------------------------|----------------------|---|---------------------------------|-----------------|
| WG | 300 – 1,300 (11¾ – 51¼) | 1,400 (3,100) | 180 – 210 (2,611 – 3,046) | 3,000 (6,600) | 57300044 |
| WG-SR | 300 – 1,300 (11¾ – 51¼) | 1,700 (3,750) | 180 – 210 (2,611 – 3,046) | 4,500 (9,900) | 57300051 |



Small Pipe Turning Device FUG

2 separate hydraulic circuits are needed on the side of the fork lift truck.

Supplied without connecting cables to the fork lift truck.

- Makes the handling of small pipes after production more efficient.
- Up to 5 small pipes with a length of 1 m can be gripped at once.
- There is a manual adjustment to accommodate other widths. The pipes are grabbed from production vertically and can be stored horizontally due to the integrated swivel mechanism.
- As the pipes are gripped on their walls, no radial pressure is exerted on them, meaning that green products can be safely handled.

FUG

| Type | Description | Number of Pipes Pcs. | Dead Weight kg (lbs) | Hydraulic Connection Pressure bar (psi) | Working Load Limit/WLL kg (lbs) | Order-Number |
|------------|---|----------------------|----------------------|---|---------------------------------|-----------------|
| FUG | up to 5 pipes with a width of 300 mm (113/4") | 5 | 450 (990) | 180 – 210 (2,611 – 3,046) | 1,500 (3,300) | 57300006 |