



## Angeled Suction Plates WSP

For the direct coupling to the operating valve unit or the hose cylinder extension.  
Suction plates with attached foam rubber seal, including lifter for tactile steering.  
Other suction plates on request.

WSP

Type	Dimensions L x W x H mm (in)	Working Load Limit/WLL -420 mbar kg (lbs)	Order-Number
<b>WSP-150-52/15-12-98°</b>	520 x 150 x 120 (20½ x 6 x 4¾)	150 (330)	<b>52500184</b>
<b>WSP-150-70/8-11-143°</b>	700 x 80 x 110 (27½ x 3¼ x 4¼)	150 (330)	<b>42100238</b>
<b>WSP-150-70/11-17-143°</b>	700 x 110 x 170 (27½ x 4¼ x 6¾)	150 (330)	<b>42100126</b>
<b>WSP-150-85/7-7-135°</b>	850 x 70 x 70 (33½ x 2¾ x 2¾)	150 (330)	<b>52300018</b>
<b>WSP-150-70/13-10-143°</b>	700 x 130 x 100 (27½ x 5 x 4)	150 (330)	<b>52500131</b>
<b>WSP-150-90/10-14-93°</b>	900 x 100 x 140 (35½ x 4 x 5½)	150 (330)	<b>52300033</b>

Caution: It is forbidden to use suction plates with a smaller working load limit than the lifting unit HE to ensure that the lifting unit is not detached. It is permissible to use suction plates with a higher working load limit than the lifting unit.