

max. 150 kg/330 lbs



MM-150-GREENLINE with Vacuum Turbine Unit, Lifting Hose Unit, Operating Unit, Hose Cylinder Extension and Suction Plate

MULTIMOBIL MM

The slim all-rounder for landscaping. Transport's concrete and natural stone elements and bulk material.

The narrow laying trolley moves large loads directly to the laying location quickly and without effort. Even to places where no other vehicle can go! Due to the narrow vehicle width of only 700 mm (27½ inch), the MULTIMOBIL MM can also get through normal doors and thus also into private gardens.

The two interchangeable bodies (1. Interchangeable body with mast and articulated boom, 2. Interchangeable body with tiltable/interchangeable body) can be changed easily, quickly and without tools by one person thanks to the practical body change system.

MM-150-GREENLINE



Type	Description	Type of Drive Diesel Engine kW	Type of Drive electric/ Battery kW	Load Extension mm (in)	Width mm (in)	Driving Speed km/h (mph)	Weight Dead Weight kg (lbs)	Pay- load kg (lbs)	Working Load Limit/ WLL kg (lbs)*	Vol- ume Shovel m³ (ft³)	Volume Hopper m³ (ft³)	Order-Number
MM-150 GREENLINE	Crawler chassis with interchangeable body with mast and articulated boom		5.5	2,600 – 2,100/ 1,700 (102¼ – 82¾/67)	700 (27½)	1.5/ 3.0 (.93/ 1.86)	770 (1,700)	400 (880)	50 – 85/ 150 (110 – 185/ 330)			43500032
MM-150-D	Crawler chassis with interchangeable body with mast and articulated boom	4.9		2,600 – 2,100/ 1,700 (102¼ – 82¾/67)	700 (27½)	1.6/ 5.2 (.99/ 3)	610 (1,350)	400 (880)	50 – 85/ 150 (110 – 185/ 330)			43500031
MM-KA	Tilting interchangeable body (Dump body and self-loading shovel – without crawler chassis)						235 (520)	450 (990)		0.05 (1¾)	0.3 (10½)	43500033



Crawler chassis of MM-D when changing the body MM-KA

MULTIMOBIL MM-150-GREENLINE

Emission-free operation thanks to electric drive – of particular advantage when working in public facilities or on construction sites with large public traffic.

Incl. interchangeable body with mast and articulated boom.

Powered by a rechargeable 48 V lithium-ion battery.

Operating time with one battery charge: 2 hours at maximum performance.

In practice, up to one day, depending on the application.

Charging time approx. 8 hours.

MULTIMOBIL MM-150-D

Crawler chassis with Yanmar diesel engine incl. interchangeable body with mast and articulated boom.

Interchangeable body 1 with mast and articulated boom:

Transport and handling of concrete and natural stone elements.

Flexible platform construction, with height-adjustable mast and articulated boom, which can be equipped with a wide range of attachment tools (see accessories).

If required, the platform superstructure can be placed on supports so that the laying work can also be carried out without the chassis. The optional counterweight set MM-GS ensures the necessary stability. A second person can thus work in parallel with the crawler chassis and the tilting / interchangeable body.

Interchangeable body 2 with tilting / interchangeable body MM-KA:

For transport of bulk materials.

Optionally available tipper body with hydraulically tipping trough, hydraulic actuated self-loading bucket, quick-change couplings for the 4 hydraulic connections and 4 telescopic supports for parking the body.

The articulated boom of the platform superstructure can be extended with different attachment tools.

These items are:

Attached to the electric wire rope hoist (230 V, wired):

- Mechanical grab, e.g. EASYGRIP EXG/EXG-MAXI Border Stone Handle.
- Ergonomic Vacuum Control Unit VS-ERGO-SPS-50-29/22 in conjunction with SPEEDY VS as vacuum generator.
- STONEMAGNET SM-600-GREENLINE/SM-600-GREENLINE-POWER.

Combined with the vacuum generator VGE-230 on the loading area:

- Vacuum Lifting Hose Units HE-35 to HE-150, Operating Valve Unit BE-Sprint-2, Ergonomic Vacuum Control Unit BE-ERGOSPRINT, Hose Cylinder Extension SZV with corresponding suction plates.

Accessories

Type	Description	Type of Drive electric/ AC (50 Hz) kW	Electric Connection/AC (50 Hz) Voltage V	Weight Dead Weight kg (lbs)	Working Load Limit/ WLL kg (lbs)	Order-Number
Rope hoist		0.75	230	22 (50)	200 / 400 (440 / 880)	43500036
MM-GS	Consisting of 4 x 60 kg (132 lbs) individual weights. For operation on MM-150-GREENLINE and MM-150-D without crawler chassis.			240 (530)		43500054

*Working load limit depending on the inserted load extension.