



Column Handles PVZ-V

Especially suitable for the carrying and laying of round and rectangular concrete or wooden columns.

- Clamping is independent of the length.
- Constructed in such a way that the columns can be set close enough to touch one another.
- The PVZ-V is an adjustable model.
- Galvanised finish.

PVZ-V

| Туре | Length of Gripper mm (in) | Dead Weight kg (lbs) | Gripping Range mm (in) | Working Load Limit/WLL kg (lbs) | Order-Number |
|-------|------------------------------|-------------------------|-----------------------------|------------------------------------|--------------|
| PVZ-V | 80 (3.15) | 8 (18) | 100 – 305 (3.94 – 12.01) | 150 (331) | 53200031 |



Stone Pillar Grab SLS-8/20-G-VA

Stone pillars and palisades, mainly made of attractive natural stone such as granite, become increasingly popular in horticulture and landscaping. For efficient installation the handy stone pillar grab SLS-8/20-G-VA was designed.

Suspended to a lifting device, such as a mini excavator, the horizontal pillar is clamped through a crank handle. The gripping force automatically increases while lifting and the pillar can be raised safely and installed easily.

After installation the crank is to be released.

- The lifting eye can be adjusted to the center of gravity of the product being lifted to let it hang vertically.
- Double-sided, non-marking rubber grippers, thus no claw marks or scratches on pillars and palisades.
- Durable surface protection by galvanizing.

SLS-8/20-G-VA

| Туре | Dead Weight kg (lbs) | Gripping Range mm (in) | Working Load Limit/WLL kg (lbs) | Order - Number | |
|---------------|----------------------|------------------------|---------------------------------|----------------|--|
| SLS-8/20-G-VA | 12.5 (28) | 80 – 200 (3.15 – 7.87) | 300 (661) | 53100409 | |

Accessories:

| Туре | Description | Dead Weight kg (lbs) | Order - Number |
|--------|--|----------------------|----------------|
| GB-SLS | Rubber grippers to retrofit stone pillar grab SLS-10/20 (Order-Nr. 53100321) equipped as standard with steel pads. Rubber grippers will not cause damage to the stone elements — gripping range is then reduced from 80 to 180 mm (3.15 to 7 inch). | 0.6 (1.32) | 43101415 |