



Pillar Swing Crane ASSK

Same specifications as Wall Swing Crane AWSK, but slewing range 270°, length and working load limit see tabel.

Important notice:

The assumption for mounting the pillar swing crane using the set of dowels is minimum thickness of the concrete floor of 200 mm (73/4") and a concrete quality C20/25. (Simple installation, no flange plates needed).

Crane height up to bottom edge of crane boom 3200 mm.

Optional accessories:

Set of dowels DS-ASSK, consisting of the following components:

Special Anchor with mortar cartridge and bush-es, 8 times threaded M 12, thickness of plate min. 8 mm (1/3") max 25 mm (1").

ASSK



ASSK

Type	Load Extension mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Angle Pivoting-/Rotation Angle °Degree	Order-Number
ASSK-150-4	4,000 (157½)	167 (370)	150 (330)	270	42000146
ASSK-150-5	5,000 (196¾)	222 (490)	150 (330)	270	42000147
ASSK-300-4	4,000 (157½)	327 (720)	300 (660)	270	42000124
ASSK-300-5	5,000 (196¾)	414 (910)	300 (660)	270	42000125

Accessories

Type	Description	Order-Number
DS-ASSK	Set of dowel for pillar swing crane	42000100