



SRZ-M

Manhole Frame Clamp SRZ-M

Lightweight, efficient and profitable – Ideal for repair and maintenance of manhole frames and compensation rings.

- Grips from the inside, with removable handles.
- Automatic release for fully-automatically switch over from „full“ to „empty“.
- With lifting eye for attaching to crane hook.
- Durable surface protection by galvanizing.

Type	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
SRZ-M	20 (45)	200 – 620 (7¾ – 24½)	150 (330)	54000033



SRZ-KOMBI. left: Hook A, right: Hook B

Manhole Frame Clamp SRZ-KOMBI

A clamp for frame and cover! Easy and safe transport and installation of manhole covers in accordance with EN 124/DIN 1229.

Both the frame and the cover can be lifted and installed safely.

The lifting eye on the shaft frame clamp is attached to the load hook on the digger/loader and placed on the manhole cover. After releasing the safety catch, the frame is lifted with the cover and placed on the shaft cone.

When the manhole cover is put down, the safety catch clicks into place by itself and the clamp opens automatically.

- By turning through 180°, the covers can also be effortlessly lifted out of the frame with the shaft frame clamp and the 2 A hooks and 2 B hooks included as standard.
- Durable surface protection by galvanizing.

Type	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
SRZ-KOMBI	15 (35)	750 / 785 (29½ / 31)	200 (440)	53100373