



SVZ-UNI



SVZ-UNI

## Manhole and cone installation clamp SVZ-UNI

This universal manhole and cone clamp SVZ-UNI enormously rationalizes transport and installation of manhole elements.

Especially suitable for manhole bases, rings (height 500 mm or larger) and cones with inner diameters of:

**SVZ-UNI:** 625/700/800/1.000/1.050/1.200/1.250/1.350/1.500 mm

**SVZ-UNI-UK:** (725/800) 900/1.000/1.050/1.200/1.250/1.350/1.500 mm

- NEW: now with additional suspension position for a more horizontal hanging of the cones.
- An additional operator is not necessary as the driver of the lifting machine „switches“ the SVZ-UNI from gripping to releasing by a slight movement of the lifting hook.
- The settings to the required diameters of the products is done very quickly through plug bolts. A rearrangement of the settings is not necessary when handling manhole rings and cones, as the SVZ-UNI has got two gripping levels.
- Efficient and economic handling of all kinds of manhole elements.
- High tensile chain suspension with eyelet.
- Durable surface protection by galvanizing.

Type	Description	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
<b>SVZ-UNI</b>	global	625 – 1,500 (24½ – 59)	103 (225)	2,500 (5,500)	<b>54000046</b>
<b>SVZ-UNI-UK</b>	UK	900 – 1,500 (35½ – 59)	96 (210)	2,500 (5,500)	<b>54000047</b>

## Accessories

Type	Description	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Order-Number
<b>SVZ-Set for adaptors</b>	surcharge for nominal width	1,800 (70¾)	25 (55)	<b>44000064</b>
<b>SVZ-UNI-AS</b>	Set of Adaptors for height support, in order to also grip rings with 250 mm height.		5.4 (10)	<b>44000079</b>