



## Lifting Hose Units HE

For use with the JUMBOMOBIL JM, JUMBO-BV, TRANSMOBIL TM, MULTIMOBIL MM, JUMBO Travelling Crane JWK or on any other crane carrier.

(Application of lifting hose unit HE-250 is permissible at stationary crane facilities only, not to be operated with JUMBOMOBIL and JUMBO-BV).

Consists of:

Transportation hook.

Rotational Device and quick coupling, 2 inch.

Lifting hose unit with protective fabric as well as a flange for fitting onto the operating valve unit.

Available optionally for HE-150/200/250: reinforced belt stay with buckle.

HE-35 – HE-250

5

Type	Diameter mm (in)	Height Lifting Height mm (in)	Working Load Limit/WLL -420 mbar kg (lbs)	Order-Number
HE-35	120 (4¾)	1,700 (67)	35 (75)	42100001
HE-50	140 (5½)	1,700 (67)	50 (110)	42100106
HE-85	178 (7)	1,700 (67)	85 (185)	42100002
HE-150	230 (9)	1,500 (59)	150 (330)	42100132
HE-200	250 (9¾)	1,500 (59)	200 (440)	42101114
HE-250	300 (11¾)	1,500 (59)	250 (550)	42101115



## Operating Valve Unit BE-Sprint-2

For direct coupling onto the lifting unit HE.

Longer operating handles on request.

### Scope of delivery

**BE-Sprint-2:** Main body with handle 500 mm long, fixing screw for adjusting the hovering position, safety gauge.

BE-Sprint-2

Type	Description	Dead Weight kg (lbs)	Order-Number
BE-Sprint-2	for HE-35 up to HE-250	8.5 (20)	42100539