

UNIMOBIL UM Laying Dolly

The UNIMOBIL UM is an installation dolly that can easily handle concrete and natural stone units up to 150 kg.

- Efficiency is noticeably increased, as it only requires one person to carry out the installation work.
- **Special feature:** The boom is lifted through a gas spring with integrated brake and is controlled by a lever on the operating handle. This way stone can be picked up from a pallet of approximately 900 mm height. By pressing the lever again the load is lowered gently into place. Pressing the lever once more lifts the boom up to pick up the next unit.

Basic version, standard equipment:

- Big rubber wheels with a diameter of 400 mm, makes manoeuvring the UM easy.
- Adjustable wheel distances (from 610 – 905 mm outside measurement) so that the UM can be adjusted to different slabs.
- Supported by a steering roller with a locking brake.
- Boom and handles are telescopic to adjust well to different weights and measures of the slabs.
- Gas spring with integrated brake with a control handle.

Please note: basic version has to be equipped with "Load Pick-up" module, in order to be used for laying slabs!

max. 150 kg

UNIMOBIL UM-SM Laying Dolly – Complete Version

Equipped with battery driven STONEMAGNET SM-600-GREENLINE. The UNIMOBIL UM-SM is the perfect vacuum laying system for slightly porous slabs and stone.

Suction plate not included in scope of delivery.

If you are already using a SM please ask us for a quotation to upgrade it to a UM-SM.

Complete version consisting of: UM-SM + SM-600 or SM-600-POWER

- The most gentle and the closest positioning of slabs as possible. Re-pick up possible. Also suitable for slightly porous stones.
- It is equipped with handles on the suction plate and a 90° turnable suspension for the perfect positioning of the slabs.
- Durable surface protection by galvanizing.



UM-SM

Type	Description	Working Voltage V	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
UM-SM	Basic version for installing the STONEMAGNET SM		42 (95)	150 (330)	42740011
SM-600-GREENLINE	Basic device, without suction plate	12	34 (75)	600 (1,320)	52720006
SM-600-GREENLINE-POWER	Basic device, without suction plate	12	35 (75)	600 (1,320)	52720007