



STAZ-UNI-P



STAZ-UNI-KA

Fork Lift Grab STAZ-UNI-P/STAZ-UNI-KA

Specially designed for the heavy duty work with forklift truck, directly fixed to the carriage plate of the forklift.

We recommend the use of a side-shift built into the forklift.
Supplied without connecting hoses to the forklift-truck.

- Light-weight, yet with a high working load limit due to the use of high-tensile steel for load bearing parts.
- Can fit all the usual packs of building materials due to a large opening range and to the exchangeable grippers which come in various lengths and designs. Fully hydraulic parallel opening range.
- Low maintenance steel polyamide sliding guides.
- Manually adjustable pressure relieve valve.
- Oil Pressure Gauge.
- Polyamide sliding guides come with a 5 year guarantee.

At **STAZ-UNI-P-1000**: grips the pack by pressing it towards the gripper close to the forklift. This achieves smallest possible load center of the pack.

At **STAZ-UNI-KA-1000**: moves both grippers synchronized towards the pack. Compact design due to integrated crane boom.

Type	Inside Height mm (in)	Dead Weight kg (lbs)	Opening Width Main Gripper mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
STAZ-UNI-P-1000	1,000 (39¼)	440 (970)	580 – 1,260 (22¾ – 49½)	2,300 (5,100)	57000087
STAZ-UNI-KA-1000	1,000 (39¼)	690 (1,520)	370 – 1,370 (14½ – 54)	2,000 (4,400)	57000107

Larger or modified opening widths and heights are available on request.



ASZ

Sorting Clamp ASZ

This universal outsourcing clamp has a wide adjustable opening width and can be used for a wide range of products.

There are two different variations:

1. ASZ for the efficient outsourcing of concrete steps, kerb stones and similar.
2. ASZ-R for the handling of sewerage elements. The grippers are prism-shaped to grip the round contour of the rings.

Please note: Designed and suitable to grip single stones or elements only. This is not the proper equipment for handling a complete row of stones.

- Lifting eye for attaching to crane hook.
- Lifting handle.
- Handle with turning range 90° depending on space.
- Exchangeable rubber metal bars, to suit the requirements.
- Automatic release for fully automatic switch-over from "full" to "empty".