



FTZ-MULTI-15: top with FTZ-MULTI-15-WB-G-120,
bottom with FTZ-MULTI-15-WB-SQ

Grab for Prefabricated Concrete Products FTZ-MULTI

**Mechanical grab. Appropriate clamp configurations for versatile applications from a modular construction system.
Same features as per FTZ-I/UNI.**

FTZ-MULTI-15: Basic unit without grippers.

- Extraordinary large gripping range, thus suitable for gripping nearly all kind of standard concrete elements and natural stones.
- The individual modules are available separately and hence a huge range of applications can be covered at a reasonable price.
- Durable surface protection by galvanizing.

6

Type	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
FTZ-MULTI-15 Basic Device	98 (215)	1,500 (3,300)	53100348

Accessories:

FTZ-MULTI-15-WB-G-42: Large gripping range, short rubber grippers - preferably suitable for handling of single elements.

FTZ-MULTI-15-WB-G-120: Large gripping range, large rubber grippers - preferably suitable for handling offull layers, such as one layer of kerb stones.

FTZ-MULTI-15-WB-SQ: Special interlocking steelfinger grippers allow for safe installation of roughly-cut ashlar rocks.

Adjustable Height Stop HVA-FTZ/TSZ: for all versions of FTZ-UNI/MAXI/MULTI and TSZ-UNI. Adjustable range TSZ-UNI/MAXI approx. 55 – 140 mm (2¼ – 5½ inch). Adjustable range FTZ-UNI/MAXI-25 and FTZ-UNI/MULTI-15 approx. 120 – 255 mm (4¾ – 10 inch).

FTZ-UNI-50 approx. 55 – 155 mm (2¼ – 6¼ inch). FTZ-MAXI-50 approx. 55 – 195 mm (2¼ – 7¾ inch).

Type	Description	Length of Gripper mm (in)	Inside Height mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Order-Number
FTZ-MULTI-15-WB-G-42	(pair)	420 (16½)	255 (10)	15.12 (35)	200 – 1,250 (7¾ – 49¼)	43100942
FTZ-MULTI-15-WB-G-120	(pair)	1,200 (47¼)	255 (10)	46 (100)	200 – 1,250 (7¾ – 49¼)	43100943
FTZ-MULTI-15-WB-SQ	(pair)		300 (11¾)	33 (75)	200 – 1,200 (7¾ – 47¼)	43100941
Adjustable Height Stop HVA-FTZ/TSZ				2.5 (6)		43100867