

max. 25 kg



FXES-25

FLIEGUAN-ERGO-STICK FXES Tile and Slab Laying Device

The new vacuum laying device for laying slabs and tiles by hand and on 2 wheels, in a way that is simple, smooth and easy on the back.

- Made of aluminium, therefore light and manageable.
- Can be connected to standard industrial vacuum cleaners (wet/dry vacuum cleaner with bypass valve for permanent cooling) using the vacuum hose and connecting cone supplied, or directly to the SPEEDY, QUICKJET or POWERJET with the vacuum hose. One easy finger movement opens a vacuum valve to release the tile/slab.
- The distance from wheel axle to suction plate can be adjusted depending on the slab size.
- Max. tile size approx. 1,000 x 1,000 mm.
- With wheel set as standard. This can be converted quickly and easily from slab to tile laying, so that the tile can be positioned with a slight forward tilt when moved.
- With smooth plastic wheels with rubber treads.
- The wheel set can be removed completely in a few steps, for example in order to lay light tiles or slabs.
- By means of the quick release, the working height of the FXES-25 can be adjusted individually.
- In addition, the handle can be set to the optimal, ergonomic working position using 2 wing nuts.

Scope of delivery

FXES-25: 1 x feed hose of DN 32 (internal diameter 32 mm) 5 m long, 2 x connecting cone for different commercially standard industrial vacuum cleaners, 1 x expander tensioner 1.5 m long.

Type	Description	Dimensions L x W mm (in)	Dimensions Stone/Element L x W mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL -150 mbar kg (lbs)	Order-Number
FXES-25	incl. Suction plate 25 kg	270 x 270 (10¾ x 10¾)	1,000 x 1,000 (39¾ x 39¾)	6 (15)	25 (55)	58500005

Accessories

Type	Description	Dead Weight kg (lbs)	Order-Number
FFS	Radio remote control set comprising transmitter and socket to switch the industrial vacuum cleaner on and off. Transmitter can be attached with Velcro. Plug type F, 230 V. Not suitable for QUICKJET and SPEEDY.	0.27 (1)	48500016