




AKZ-H-UNIGRIP



AKZ-UNI-H

Block Loading Grabs AKZ with Adjustable Height

This has the same design and characteristics like the AKZ-UNI but comes with adjustable height for differing pack heights.

This universal type of grab is suitable for the transport of building materials of all types and sizes. By the adjustable height and the large opening width it can be used for all building materials on pallets and without pallets.

Height Adjustment with a choice of fixed or floating position.

A choice of various heights.

The vertical height adjustment bar is equipped with 4 drillings which are situated on different height levels, each shifted by 90°.

Locking the grab onto position (Locking Mechanism).

The desired height is set by means of the practical star handles. Once the grab has been raised, the height adjustment locks into position automatically when it has reached the required height.

Advantage: The grab can be squeezed in between tightly-packed blocks of goods.

The different levels are for the following heights:

level 1 (turning 0°) R 1,100 mm (43")

level 2 (turning 90°) R 1,280 mm (50")

level 3 (turning 180°) R 1,470 mm (58")

level 4 (turning 270°) R 1,650 mm (65")

Extending the legs to the required height (floating position).

The desired height is set by means of the star handles. Once the grab has been raised, the legs extend to the required measurements, once the grab is put back down, the legs revert to their lowest position.

Advantage: Once the goods have been unloaded, the grab height does not need to be adjusted manually to return to the optimal low resting height.

Time savings: The driver does not need to leave the cab to set down the grab.

Higher pressure – finely adjustable, for example to grip material which is sensitive against pressure.

Low overall height of equipment.

- Hydraulically and smoothly operable and works in parallel.
- Robust gear rack balance for the absolute synchronous running of the hydraulic cylinders.
- Large low-maintenance polyamide sliding guides with 5-year guarantee.
- Automatic pressure control.
- Working load limit of height-adjustable versions in retracted position will be increased as per positive working automatic pressure control up to the respective figure indicated in brackets.
- Manually adjustable pressure-reducing valve.
- Oil pressure gauge.
- 4 hanging eyes for cables or straps/belts.
- Light-weight construction in high-tensile steel.

Type	Inside Height mm (in)	Dead Weight kg (lbs)	Hydraulic Connection Pressure bar (psi)	Opening Width mm (in)	Working Load Limit/ WLL kg (lbs)	Gripper Base Length mm (in)	Order-Number
AKZ-H-UNIGRIP	1,100 – 1,650 (43¼ – 65)	380 (840)	180 – 210 (2,611 – 3,046)	370 – 1,370 (14½ – 54)	1,900 / 1,350 (4,200 / 3,000)	720 (28¼)	56100057
AKZ-UNI-H*	1,100 – 1,650 (43¼ – 65)	385 (850)	180 – 210 (2,611 – 3,046)	370 – 1,370 (14½ – 54)	1,900 (4,200)	720 (28¼)	56100101

* Expected to be available from the beginning of Q3 2022