

Hollow Block Handles FSZ-M – not merely for hollow core block, but also for drain elements, U stones, etc.

FSZ-M:

- Can be attached to hoists or can be carried by two workers
- Depending on the space available at the site, the handle can be rotated by 90°
- Large adjustment range for general use
- With automatic release (refer to page 72)



FSZ-M

Type	Gripping Range* W in (mm)	Working Load Limit WLL lbs (kg)	Dead Weight lbs (kg)	Order-Number
FSZ-M ①	7 - 22 3/4" (180 - 580)	550 (250)	35 (16)	53200002



RGV-9/9

Turf Stone Laying Clamp RGV

Laying Clamp for Turf Stones, versatile due to exchangeable adaptors.

- RGV-9/9 fits Turf Stones 60 x 40 cm, hole dim. 9 x 9 cm
- Installs 1 to 5 units at once
- Alternating "on-off" switching with Probst's indestructible automatic release simplifies your work: No user required to switch from "grip" to "release" (refer to page 72)
- Lifting eye, handle, turnable by 90°
- Screwable adaptors – not compatible with TSV!

Type	Description	Gripping Range* W in (mm) depending on adaptors	Working Load Limit WLL lbs (kg)	Dead Weight lbs (kg)	Order-Number
RGV ①	Basic unit, without adaptors	approx. 2 3/4" - 20" (70 - 500)	250 (550)	30 (15)	43101154
RGV-AS-9/9	Adaptors for 9 x 9 cm		250 (550)	11 (5)	43101153
RGV-9/9 ①	Complete unit, RGV+RGV-AS-9/9	12 - 20" (300 - 500)	250 (550)	44 (20)	53100372

For an enquiry concerning the required adaptor set, please send us a dimensioned drawing of the block used.

① Durable surface protection by galvanizing

* Gripping range indicates the minimum and maximum pack measurements of building materials, which can be picked-up with this grab