



RKZ-H

Ring- and Cone Clamp RKZ-H

A hydraulic grab attachment for transporting up to 3 manhole rings with a height of 500 mm (19½ inch).

An adjustment to the widths is done hydraulically prior to the clamping action. This hydraulic change-over means that to operate the clamping and diameter setting action, only one hydraulic circuit is needed on the side of the fork lift truck.

The RKZ-HS is a heavy-duty model for up to 4 manhole rings with a height of 500 mm (19½ inch). Supplied without connecting hoses to the fork lift truck.

If possible the Ring- and Cone Clamp RKZ-H/HS should be fitted onto the fork lift truck with a crane boom and a hydraulic rotator.

- Can also be used for single manhole cones due to its swinging grippers.
- Ideal for clearing the manufacturing area and for loading trucks.
- By clamping onto the walls of the products no radial pressure is exerted on the rings and so fairly green products can be removed from the manufacturing surface at a much earlier stage.

Type	Diameter Nominal Diameter mm (in)	Inside Height mm (in)	Dead Weight kg (lbs)	Hydraulic Connection Pressure bar (psi)	Working Load Limit/WLL kg (lbs)	Order-Number
RKZ-H	600 – 1,500 (23½ – 59)	1,500 (59)	680 (1,500)	180 – 210 (2,611 – 3,046)	1,750 (3,850)	57200011
RKZ-HS	600 – 1,500 (23½ – 59)	2,000 (78¾)	790 (1,740)	180 – 210 (2,611 – 3,046)	2,300 (5,100)	57200012



RKG

Ring- and Cone Clamp RKG

Hydraulically operated universal grab attachment for manhole rings and cones.

Using only one hydraulic circuit the clamp firstly adjusts to the inner diameter and then clamps the ring wall by 3 hydraulically operated rubber-lined gripping claws.

Supplied without connecting hoses to the fork lift truck.

If possible, the Ring- and Cone Clamp RKG should be attached to the fork lift truck with a crane boom and a hydraulic rotator.

- As no radial pressure is exerted, it is possible to handle green products.
- Suitable for use with fork lift trucks as well as loading cranes.

Type	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Hydraulic Connection Pressure bar (psi)	Working Load Limit/WLL kg (lbs)	Order-Number
RKG-20	600 – 2,000 (23½ – 78¾)	600 (1,320)	180 – 210 (2,611 – 3,046)	2,500 (5,500)	57200002
RKG-25	600 – 2,500 (23½ – 98½)	620 (1,370)	180 – 210 (2,611 – 3,046)	2,500 (5,500)	57200187
RKG-S-25	600 – 2,500 (23½ – 98½)	655 (1,440)	180 – 210 (2,611 – 3,046)	4,000 (8,800)	57200110
RKG-S-30	600 – 3,000 (23½ – 118)	820 (1,810)	180 – 210 (2,611 – 3,046)	3,000 (6,600)	57200094