


Hydraulic Laying Clamp VZ-H-UNI – The all-rounder for virtually all elements

- Curb stones can be gripped lengthways or across depending on the space conditions
- Special jaws for rocks, turf stones and similar, easy and quick to attach
- Use generally on diggers or laying machines with a hydraulic rotary head



VZ-H-UNI-KV


Type	Specification	Gripping Range in (mm)	Working Load Limit WLL lbs (kg)	Dead Weight lbs (kg)	Order-Number
VZ-H-UNI-KV Full version ①	incl. clamping unit, 1 set of rubber grippers and 1 set of steel finger grippers, continuous rotator, suspension, set of hydraulic hoses	1½ – 22½" (40 - 570) up to 39 – 59" (1,000 - 1,500)	1,100 (500)	375 (170)	51600031-002
VZ-H-UNI-FG ①	Rock grippers (in pairs)		1,100 (500)	50 (22)	41600160
VZ-H-UNI-RG ①	Gripping adapter for grass stones and large-seized slabs (in pairs)		1,100 (500)	30 (14)	41600176
VZ-H-UNI-GBL ①	Rubber gripper with larger inside height			10 (4.4)	41600151



VZ-H-UNI-FG



VZ-H-UNI-RG



German Patent

GR-150

Slipform for Concrete Backfill of Curbs GR-150 – standardized backfill in minutes

The GR puts an end to laborious backfill work on the construction site. DIN 18318 mandates slip formed backfill.

- Cam lever releases and tightens casing sheet
- Can be adjusted to all conventional curb stones
- Tamper included as standard
- **Saves time and concrete!**

Type	Length of form sheet in (mm)	Thickness of backfill in (mm)	Thickness of kerb stones in (mm)	Dead Weight lbs (kg)	Order-Number
GR-150 ①	59 (1,500)	6 (150)	3 1/4 - 7 3/4" (80 - 200)	75 (33)	51000066
KS-GR-150 ①	Link rod for slipform			2 (1)	41000241

GUTTERFIX RF-H Screeding System for lean concrete – perfect gutter bedding

Professional tool for roadwork. Eliminates time consuming conventional removal with shovels.

- Ball-bearing mounted rollers for ease of adjustment and accuracy
- Adjustable to all conventional curb stone thicknesses and heights

Type	Working Width max. in (mm)	Suitable for Kerb Thickness in (mm)	Ground Level from Top of Kerb in (mm)	Dead Weight lbs (kg)	Order-Number
RF-H ①	max. 19 3/4" (500)	4 3/4" – 7 3/4" (120 - 200)	2 3/4" – 11 3/4" (70 - 300)	30 (13)	51000064



RF-H

① Durable surface protection by galvanizing