Suction Plates SPS for Lifting Device SH / **POWERJET PJ-1650**

For different jobs we recommend special suction plates. All suction plates can be changed by means of a quick release coupling (modular principle). The carrying capacities depend on the size of the suction plate. The Probst special foam-rubber seal is suitable for all types of materials:

- Particularly good with uneven surfaces
- Extremely durable
- Changed in a flash: take the old one off, put on the new one - finished!

Туре	Suction Plate Dimension in (mm)	Working Load Limit WLL* Ibs (kg)	Working Load Limit WLL** Ibs (kg)	Order- Number
SPS-3500(2300)-174/92 •	69 x 36 (1,740 x 920)	7,700 (3,500)	5,100 (2,300)	42400555
SPS-2500(1650)-143/78 0	56 x 30 ¾" (1,430 x 780)	5,500 (2,500)	3,650 (1,650)	52500239
SPS-1200(800)-96/58 •	37 ³ / ₄ " x 22 ³ / ₄ " (960 x 580)	2,650 (1,200)	1,760 (800)	52500162
SPS-1010(670)-84/57 0	21 1/4" x 22 1/2" (840 x 570)	2.230 (1.010)	1.480 (670)	52500238

SPS-1200(800)-96/58





Туре Description Working Load Limit WLL*** Order-Number lbs (kg) TRA-3500 For multiple use of the suction plates single 7,700 42500260 plates adjustable. Suction plate turnable (3.500)Spreader Distance between centres of suction plates adjustable from max. 1,450mm to min.

More than 1.000 different suction plates are available.

• Durable surface protection by galvanizing

TRA-3500 Spreader Bar for attachment of 2 suction plates

Thanks to use of the vacuum traverse TRA-3500, concrete slabs weighing up to 3,5 tonnes can be lifted easily by just one person and placed down exactly where required. It is no longer necessary to grasp under the slab – it doesn't get better or more rational than this! A large selection of suction plates from the Probst range are available.

Accessories SH-2500 / SH-3500

Туре	Description	Dead Weight lbs (kg)	Order- Number
SH-AD	Retrofit kit with Rotator Baltrotor	97 (44.1)	42500267

^{***} Caution: Take note of the carrying capacity of the vacuum-lifting device.