

Vacuum Lifting Device SH-1000-MINI – Optional sources: powered electrically, hydraulically or by integrated gas engine

For efficient and safe handling and laying of heavy loads up to 1,000 kg, such as granite slabs, dense concrete elements, marble slabs, kerb stones, steps, pipes etc.

- Can be hooked in to any carrier or laying machine VM by means of load hook, chain, hoisting cable or similar
- All-purpose lifting device · One-man operation
- By means of rapid change fasteners different suction plates can be attached to the SH within seconds for varying kinds of applications, various slab dimensions and weights
- Operating handles are arranged in ergonomic position for convenient direction and handling. Handles can easily be rearranged into a rack to put down the device on the ground properly
- Fitted as standard with chain compartment and safety chain

Working
Load Limit
2,200 lbs



SH-1000-MINI-E

Type	Power	Working Load Limit WLL (depending on the suction plate used) max. lbs (kg)*	Dead Weight lbs (kg) (without suction plate)	Order- Number
SH-1000-MINI-H	hydraulic	2,200 (1,000)	200 (91)	52400040
SH-1000-MINI-B	integral petrol engine	2,200 (1,000)	200 (90)	52400018
SH-1000-MINI-E	electric, 110 v, 60 Hz	2,200 (1,000)	195 (89)	52400020



SH-1000-MINI-B



SH-1000-MINI-H

* Value at 600 mbar low pressure.

More than 1.000 different suction plates are available, see page 49 for examples.