

Vacuum Lifting Device SH-2500-UNI – The classic

- Having been designed specifically for harsh construction site use, this classic has proven itself on countless construction sites worldwide
- Integrated gas engine power (Honda). 110v power available as an option
- Suitable for predominantly wet-cast concrete and natural stone elements
- Vacuum plate seals can be replaced in minutes without gluing – simply take off the old seal and put on the new one
- Wear-resistant sponge rubber seal, adapts perfectly to uneven surfaces
- Fitted as standard with chain compartment and safety chain

Options: Wheelset SH-2500-RS and retrofit kit with rotator Baltrotor SH-AD (refer to page 49)

Type	Power	Working Load Limit WLL* lbs (kg)	Dead Weight (without suction plate) lbs (kg)	Order-Number
SH-2500-UNI-B	gas engine 2,9 kW	5,500 (2,500)	265 (120)	52400043
SH-2500-RS	wheelset for all models SH-2500-UNI			42500299



SH-2500-UNI-B

Vacuum Lifting Device SH-2500-GREENLINE – the innovative green rechargeable powerhouse

The classic now also with battery drive. Powerful and independent of mains power.

- Emission-free and low-noise operation
- Powered by a 24 V lithium-ion rechargeable battery. (exchangeable battery concept) can operate up to 6 hours
- Suitable for predominantly wet-cast concrete and natural stone elements
- Fitted as standard with safety chain

Options: Retrofit kit with rotator Baltrotor SH-AD (refer to page 49)



SH-2500-GREENLINE



More than 1.000 different suction plates are available, see page 49 for examples.

Type	Description	Power	Working Load Limit WLL* lbs (kg)	Dead Weight (without suction plate) lbs (kg)	Order-Number
SH-2500-GREENLINE	Basic device, without suction plate	by 24 V battery	5,500 (2,500)	285 (130)	52400046
SH-2500-GREENLINE-FFS	Basic device, without suction plate. With remote control	by 24 V battery	5,500 (2,500)	285 (130)	52400048