



HiVIZ

Type	Description	Dead Weight lbs (kg)	Order-Number
84 ft Bundle	(12 x 7 ft Sections)	41 (19)	51800118
Single 7 ft bundle		1.5 (3)	51800118

HiVIZ™ Safety Edge Restraint

Make your display safer by using a transitional strip. The HiVIZ sits on floor to meet the top of your display, reducing tripping and holding it together.

- Great for tradeshow and displays
- Safety bright yellow PAVE EDGE

Permeable Application: PICP GEO-GRIP WRAP Method- It's all about the wrap!

Introduced in 1997, the Geo-Grid Wrap Method was designed to address securing the edging to the base without the use of spikes. Sections of the Geo-Grid are laid on top of the base (under the edging, bedding, and pavers), then wrapped around PAVE EDGE Industrial, Rigid, or Flexible and brought back under the pavement. This eliminates the need for labor-intensive and time consuming attachment of Geo-Grid to the edge restraint. The Geo-Grid interlocks with the base, bedding, and pavers to integrate with the pavement system.

By “wrapping” PAVE EDGE edging with the Geo-Grid, you’ll create the strongest and most durable restraint throughout the permeable pavement system.

Overlay Method

- Segmental pavement installation over concrete or asphalt surface
- Overlays rehabilitate old pavements
- Pavement area can remain the same size or can be enlarged
- Details on website



Geo-Grid Wrap



Geo-Grid Wrap