

SurfaceSAVER™ Roller Plate Attachment

Leading slab manufacturers recommend roller compactors to avoid damage. The process is a gentle compression of slabs/pavers into the bedding course. Rollers dampen compaction amplitude and consolidate bedding sand or chip through higher frequency vibration. This prevents the slabs from shifting and edges from chipping. The pavement is also protected from scratches caused by scraping joint sand across the surface.

• Roller diameter: 3 3/4" (9 cm)

Secure mounting with adjustable width clamps

• SS70 Clamping Range: 15" - 22.5" (39 - 57 cm)

• SS90 Clamping Range: 15.75" - 25.5" (40 - 65 cm)

Туре	Dimensions in (cm)	Width in (cm)	Dead-Weight Ibs (kg)	Order- Number
SurfaceSAVER 70* (Frame Only)	19 x 27 ½ x 4 ½ (48 x 69 x 11)	22.8 (58)	109 (49)	41850319
SurfaceSAVER 90* (Frame Only)	19 x 34 ½ x 4 ½ (48 x 88 x 11)	30.7 (78)	138 (63)	41850320
Bracket Set (*for SS70 & SS90)				41850321
Disc-Lock Nuts (*for SS70 & SS90)				41850264
Bolts (*for SS70 & SS90)				41850258



