



AL-33-EASY-V

Block Cutters AL-EASY

AL-33-EASY-V/AL-43-EASY-V:

The required height of the stones can be set easily and quickly using a smoothly-operating handle. Improved technology resulting in effort saving of up to 20% when cutting blocks.

Blade has 4 cutting edges.

Tilting, spring-mounted supporting table allows clean undercut for precise laying without uneven large gaps.

Size indicator in centimetre and inches as well as 45-degree angle on both support plates speed up the work enormously!

AL-43/U-EASY-V:

Designs also suitable for concrete kerbstones or limestones up to height 300 mm (11¾ inch).

- Cut blocks with significantly reduced effort.
- Clean cuts with precisely guided, square, reversible blade.
- Suitable for cutting concrete paving.
- Durable surface protection by galvanizing.

Type	Width Cutting Width mm (in)	Dead Weight kg (lbs)	Height Stone/Element mm (in)	Order-Number
AL-33-EASY-V	330 (13)	42 (95)	10 – 120 (½ – 4¾)	51200059
AL-43-EASY-V	430 (17)	60 (130)	10 – 120 (½ – 4¾)	51200061
AL-43/U-EASY-V	430 (17)	73 (160)	10 – 300 (½ – 11¾)	51200064



AL-33/S-V

Block Cutters AL-33/S-V

Ideal for cutting slabs and clinker and concrete blocks.

For slightly concave or convex stone elements, e.g. such as clinker and large stone slabs with max. 4 mm height difference, minimum stone length 50 mm (2 inch) or 180 mm (7 inch), depending on the model.

- Cutting teeth adapt optimally to the surface of the block.
- The even pressure on the break line allows a much better cutting result with less force.
- Clinker with a height difference of up to 4 mm (¼ inch) in surface can therefore be snapped with no problem.
- Durable surface protection by galvanizing.

Type	Width Cutting Width mm (in)	Dead Weight kg (lbs)	Height Stone/Element mm (in)	Order-Number
AL-33/S-V	330 (13)	53 (115)	20 – 140 (¾ – 5½)	51200044