



SandScreed Pro

Sickle-shaped profile cuts the material accurately and prevents the TELEPLAN from running upwards.

Type	Length in (mm)	Dead-Weight lbs (kg)	Order-Number
SandSCREED PRO	23 - 39 (600 - 1,000)	8 (3.7)	51010006
SandSCREED PRO	39 - 65 (1,000 - 1,650)	10 (4.6)	51010001
SandSCREED PRO	59 - 102 (1,500 - 2,600)	13 (6)	51010002
SandSCREED PRO	78 - 138 (2,000 - 3,500)	15 (7.3)	51010003

FIXPLAN FP Handscreeding System New - Quick and easy planing of small and medium-sized areas

The FIXPLAN FP aluminium profile is sickle shaped. As a result the profile cuts itself into the bedding material and does not move upwards! No need for executing any force to push it down when pulling. Especially when screeding compacted sand, also in case of the screed bar cannot be moved side-ways sawing off the bedding material due to lateral obstacles or boundaries, the advantages of the FP profile are enormous with regard to effort of energy, working speed and high-quality performance of the laying course. With height adjustable height stop on both sides, range of adjustment 0- 5 in (0 - 127 mm). Can be taken off quickly if required.

- 4 screeding widths available.
- Intergrated fitting for optionally available handles HG-ERGO-DUO included in the side parts.
- With the optionally available handle HG-ERGO-SOLO, the FIXPLAN FP can also be used by just one person.
- The light-weight aluminium hollow profile is extremely sturdy (high-tensile material - weight is 1.3 kg / 3 lbs per meter).
- Long Lifespan.



FP-250 & HR-ERGO-SOLO

SandSCREED PRO™ / TELEPLAN TP

Screeds simply by pulling without the need to force the blade edge down into the bedding. Using the weight of the sand within blade's profile arc, SandSCREED PRO maintains downward pressure, keeping it's edge down for you. Use as a standard screed board or with the Handle Set. Anytime you need a straight edge, level or to verify slope, check the Built-in Level Indicator.

- Positionable Handle Brackets connects anywhere across screed
- Width adjusts without tools
- Built-in height guides (adjust from 0" - 5")
- Built-in level
- Curved design „cuts“ into bedding sand reducing lift
- Adjustable Screed Guide on both ends to screed off an existing curb, pavement, or edging



FP-150

TP/FP-RS

Type	Length in (mm)	Dead-Weight lbs (kg)	Order-Number
FP-70	27.5 (700)	5.5 (2.5)	51010015
FP-150	59 (1,500)	7.9 (3.6)	51010016
FP-200	78 (2,000)	9.5 (4.3)	51010017
FP-250	98.5 (2,500)	10 (4.5)	51010018

Accessories TELEPLAN TP / FIXPLAN FP

Type	Description	Dead Weight lbs (kg)	Order-Number
HG-ERGO-SOLO		5.7 (2.6)	41010074
HG-ERGO-DUO		9.5 (4.3)	41010072
TP/FP-RS	Set of Roller Units for TELEPLAN/FIXPLAN	2.6 (1.8)	41010080